44 CE

GEWieb

44 CE enclosures are made using **three types** of technopolymer (**two being halogen-free**) for every day, special or industrial use. Available in **11 sizes** with a standard or high-capacity back-mounting plate, a deep or plain cover (solid or transparent), smooth walls or with quick-inlet cable glands.

The exclusive advantages of the 44 CE range



Hinged cover

The boxes with plastic screws include a hinged cover. In addition, this patented solution incorporates an access hole for a security wire sealing system.



Quick-entry cable glands

Boxes with cable glands enable both rigid and flexible cables to be installed quickly, providing IP protection and excellent mechanical performance, thanks to the special "suction cup effect".



Constructed with fireresistant materials

The GWT 960°C (UL94: V0) versions are made of top quality fire-resistant material so they're suitable for technical rooms and places open to the public, and also marine or worksite (RINA certification).



1/4 turn versions

The cover is fitted with captive 1/4 turn screws and with retained lid, enabling fast and easy installation.



Discover the complete 44 CE range at www.gewiss.com



Protection in any environment

With IP56 ingress protection and selfextinguishing materials (GWT 650°C to GWT 960°C) these boxes can be used in any environment, whether indoor or outdoor - even where there is a higher fire risk.





Installation versatility

A special rib on the back-mounting plates of the box allows you to fix plates, DIN rails and terminal blocks, and the two largest versions have specific seats for quick fixing using a rivet.



High capacity

The boxes with a high capacity backmounting plate are designed to house large-diameter tubes (up to 50mm) so they're ideal for systems with a high number of connections.



Wide choice of accessories

Various accessories are available: backmounting plates in steel or an isolating material, terminal blocks, screwcaps, fixing brackets, watertight coupling device, and cable glands with or without quick entry (versions with ø 25mm).