



## Potential distributors

Potential distributor 4x DC 24 V + 4x GND

- Max. 8 A supply load
- Powers outputs using the power bus
- A blue LED indicates the module's operating status

The 4x DC 24 V + 4x GND potential distributor makes the 24 V DC supply and the GND connection from the power bus available on the front connector.

### Technical specifications

<b>General information</b>	
Order number	600-720-0DH01
Article name	Potential distributor 4x DC 24 V + 4x GND
Scope of delivery	Potential distributor 4x DC 24 V + 4x GND
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 75 g
<b>Current draw</b>	
External	Max. 0 mA
Internal	Max. 22 mA
<b>Power dissipation</b>	Max. 0.1 W
<b>Load</b>	
Per contact	8 A
Total load, 24 VDC	8 A
Total load, GND	8 A
Total load, AUX	8 A
<b>Hot-swap capable</b>	Yes
<b>Ambient conditions</b>	
Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Protection rating	IP 20
Certifications	CE, UL
<b>UL</b>	
Surrounding Air Temperature	0 °C ... +60 °C
Pollution degree	2
<b>CE</b>	
Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"

Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock“
RoHS	Yes
REACH	Yes