



## Front connector with cables, screw contacts

20-pin, 3 m

- Cable length 3 m
- Wires 0.5 mm<sup>2</sup> blue (RAL 5010)
- Numbers printed on in accordance with assignment in connector
- 20-pin

The 20-pin front connectors with cables and proven screw contacts enable simple connection of sensors and actuators to input/output modules. In this way the wiring can be kept when replacing modules.

### Technical specifications

<b>General information</b>	
Order number	700-392-1AJ10B
Article name	Front connector with cables, screw contacts, 20-pin, 3 m
Scope of delivery	Front connector with cables, 3 m
Weight	Approx. 60 g
<b>Connector</b>	
Connector type	screw contacts
Number	20
Connectible cables	Flexible and solid cables
Stripping length	6 mm
With/without ferrules	0.25 – 1.5 mm <sup>2</sup>
Tightening torque	max. 0.5 Nm
Cable length	3 m
Voltage	230 V AC
Current	3 A at 60 °C
<b>Ambient conditions</b>	
Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-25 °C ... +80 °C
Relative air humidity	max. 75 % at +25 °C
Pollution degree	2
Protection rating	IP20
Certifications	CE
<b>CE</b>	
RoHS	Yes
REACH	Yes