



- Single phase and DC input
- Short circuit, overload, input and output overvoltage protections
- Over temperature protection
- Suitable for standard applications
- Alarm contact



NOTE

Please refer to the datasheet for more details  
Above overcurrent limit, the protection starts cycling in ON/OFF mode(hiccup autoreset), the maximum current supplied depends by the line resistance



CODE	XCSL1072W024VAA	XCSL1120W024VAA
TYPE	CSL1-072W/024V/AA	CSL1-120W/024V/AA
<b>INPUT TECHNICAL DATA</b>		
Input rated voltage	120-230 Vac	120-230 Vac
Input voltage AC	85...264 Vac	85...264 Vac
Input voltage DC	100...370 Vdc (derating Uin<130 Vdc)	100...370 Vdc (derating Uin<130 Vdc)
Frequency	47...63 Hz	47...63 Hz
Current consumption	0.7 A [120 Vac] / 0.4 A [230 Vac]	1.8 A [120 Vac] / 1.1 A [230 Vac]
Inrush peak current	20 A	20 A
Power factor	> 0.65	> 0.65
Internal protection fuse	T 2 A	T 3.15 A
External protection on AC line	MCB: C-4 A / Fuse: T-4 A	MCB: C-4 A / Fuse: T-4 A
<b>OUTPUT TECHNICAL DATA</b>		
Output rated voltage	24 Vdc ±1%	24 Vdc ±1%
Output adjustable range	16 ... 28 Vdc	16 ... 28 Vdc
Continuous current	3 A at 50°C	5 A
Overload limiting	> 6 A per > 30 s	>6.2 A for >30 s
Short circuit peak current	15 A for 50 ms	15 A for 50 ms
Ripple @ nominal ratings	40 mVpp	50 mVpp
Hold up time	20 ms [120 Vac] / 70 ms [230 Vac]	20 ms [120 Vac] / 20 ms [230 Vac]
Status indication	LED "DC OK"	LED "DC OK"
Alarm contact	dry contact, max. 1A @ 24 Vdc (Uout >22.0 Vdc)	dry contact, max. 1A @ 24 Vdc (Uout >22.0 Vdc)
Parallel connection	possible	possible
Redundant parallel connection	possible with external ORing diode	possible with external ORing diode
<b>GENERAL TECHNICAL DATA</b>		
Efficiency	87% [120 Vac] / 87% [230 Vac]	85% [120 Vac] / 85% [230 Vac]
Dissipated power	10.8 W [120 Vac] / 10.8 W [230 Vac]	21.2 W [120 Vac] / 21.2 W [230 Vac]
Operating temperature range	-20...+70°C (derating -3 W/°C >50°C)	-20...+70°C (derating -3 W/°C >50°C)
Input / output isolation	3 kVac / 60 s [SELV output]	3 kVac / 60 s [SELV output]
Input / ground isolation	1.5 kVac / 60 s	1.5 kVac / 60 s
Output / ground isolation	0.5 kVac / 60 s	0.5 kVac / 60 s
Standard / approvals	EN 60950-1	EN 60950-1, EN 62368-1
EMC Standards	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4	EN 61000-6-2, EN 61000-6-4
Overvoltage category / Pollution degree	II / 2	II / 2
Protection degree	IP 20	IP 20
Connection terminal IN/OUT	2.5 mm <sup>2</sup> / 2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup> / 2.5 mm <sup>2</sup>
Housing material	aluminium	aluminium
Dimension	40x115x115 mm	40x115x115 mm
Approximate weight	400 g	400 g
Mounting information	vertical on a rail, 20 mm from adjacent components	vertical on a rail, 20 mm from adjacent components
APPROVALS		
<b>ACCESSORIES</b>		
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Mounting rail (IEC60715/TH35-15)	—	—
Marking tag	—	—