

# GEWISS

## Normkapslingar



**Malthe Winje**

08-594 118 30   [www.mwa.se](http://www.mwa.se)   [info@mwa.se](mailto:info@mwa.se)

### 40 CDe - SPANISH STANDARD SURFACE-MOUNTING AND FLUSH-MOUNTING ENCLOSURES

#### WALL-MOUNTING ENCLOSURES WITHOUT DOOR - IP40

GW40340



#### ENCLOSURES TO HOUSE ICP POWER LIMITING CIRCUIT BREAKER - WITHOUT DOOR SEALABLE - IN=40A - GREY RAL 7035

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | R.U. 1407-D<br>Classifications | Pack<br>Carton |
|-----------|----------------------------|--------------------------|--------------------------------|----------------|
| GW 40 340 | 4                          | 120x195x76               | CS-ICP32                       | 30             |

ACCESSORIES SUPPLIED: service labels.

#### FLUSH-MOUNTING ENCLOSURES WITHOUT DOOR - IP40

GW40331



#### DISTRIBUTION BOARDS TO HOUSE ICP POWER LIMITING CIRCUIT BREAKER SEALABLE - IN=40A - WHITE RAL 9016

| Code      | No. EN 50022<br>mod. ICP sect. | N. EN 50022 mod.<br>CB section | Outer dim.<br>LxHxD (mm) | R.U. 1407-D<br>Classifications | Pack<br>Carton |
|-----------|--------------------------------|--------------------------------|--------------------------|--------------------------------|----------------|
| GW 40 331 | 4                              | 8                              | 305x195x75               | CCE-ICP32                      | 10             |
| GW 40 332 | 4                              | 12                             | 372x195x75               | CCE-ICP32                      | 10             |

ACCESSORIES SUPPLIED: service labels.

#### FLUSH-MOUNTING ENCLOSURES WITH DOOR - IP40

GW40336



#### DISTRIBUTION BOARDS TO HOUSE ICP POWER LIMITING CIRCUIT BREAKER SEALABLE - IN=40A - SMOKED TRANSPARENT DOOR

| Code                            | No. EN 50022<br>mod. ICP sect. | N. EN 50022 mod.<br>CB section | Outer dim.<br>LxHxD (mm) | R.U. 1407-D<br>Classifications | Pack<br>Carton |
|---------------------------------|--------------------------------|--------------------------------|--------------------------|--------------------------------|----------------|
| DOOR COLOUR: SMOKED TRANSPARENT |                                |                                |                          |                                |                |
| GW 40 336                       | 4                              | 8                              | 329x225x75               | CCE-ICP32                      | 10             |
| GW 40 337                       | 4                              | 12                             | 400x225x75               | CCE-ICP32                      | 6              |

ACCESSORIES SUPPLIED: service labels.

GW40338



#### DISTRIBUTION BOARDS TO HOUSE ICP POWER LIMITING CIRCUIT BREAKER SEALABLE - IN=40A - BLANK DOOR

| Code               | No. EN 50022<br>mod. ICP sect. | N. EN 50022 mod.<br>CB section | Outer dim.<br>LxHxD (mm) | R.U. 1407-D<br>Classifications | Pack<br>Carton |
|--------------------|--------------------------------|--------------------------------|--------------------------|--------------------------------|----------------|
| DOOR COLOUR: BLANK |                                |                                |                          |                                |                |
| GW 40 338          | 4                              | 8                              | 329x225x75               | CCE-ICP32                      | 10             |
| GW 40 339          | 4                              | 12                             | 400x225x75               | CCE-ICP32                      | 6              |

ACCESSORIES SUPPLIED: service labels.

## 40 CDKe - GERMAN STANDARD SURFACE-MOUNTING ENCLOSURES AND BOARDS

## ENCLOSURES WITH SMOKED TRANSPARENT DOOR - IP65

GW40101



## ENCLOSURES AND DISTRIBUTION BOARDS FITTED WITH TERMINAL BLOCKS

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Pack<br>Carton |
|-----------|----------------------------|--------------------------|----------------------------------------|----------------------------------------|----------------|
| GW 40 101 | 4                          | 143x210x100              |                                        |                                        | 19             |
| GW 40 112 | 8                          | 215x210x100              | (1x25)+(7x10)                          | (1x25)+(7x10)                          | 1/12           |
| GW 40 116 | 18                         | 410x285x140              | (5x25)+(14x10)                         | (5x25)+(14x10)                         | 1/3            |

GW40119



## ENCLOSURES AND DISTRIBUTION BOARDS FITTED WITH TERMINAL BLOCKS

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Pack<br>Carton |
|-----------|----------------------------|--------------------------|----------------------------------------|----------------------------------------|----------------|
| GW 40 117 | 36 (18x2)                  | 410x463x140              | (10x25)+(28x10)                        | (10x25)+(28x10)                        | 1/2            |
| GW 40 118 | 54 (18x3)                  | 410x655x140              | (10x25)+(28x10)                        | (10x25)+(28x10)                        | 1              |
| GW 40 119 | 72 (18x4)                  | 410x878x160              | (10x25)+(28x10)                        | (10x25)+(28x10)                        | 1              |

GW40113



## ENCLOSURES AND DISTRIBUTION BOARDS FITTED WITH TERMINAL BLOCKS AND INTERCHANGEABLE FLANGES (2 FLANGES WITH KNOCKOUT HOLES) - GREY RAL 7035

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Pack<br>Carton |
|-----------|----------------------------|--------------------------|----------------------------------------|----------------------------------------|----------------|
| GW 40 113 | 12                         | 298x260x140              | (3x25)+(10x10)                         | (3x25)+(10x10)                         | 6              |
| GW 40 114 | 24 (12X2)                  | 298x420x140              | (3x25)+(10x10)                         | (3x25)+(10x10)                         | 3              |
| GW 40 115 | 36 (12x3)                  | 298x570x140              | (6x25)+(20x10)                         | (6x25)+(20x10)                         | 2              |

CHARACTERISTICS: the flanges with knockout holes have the following inputs: 4xM16; 4xM20; 3xM25; 1xM32; Glow Wire Test: 750°C

ACCESSORIES SUPPLIED: terminal block, screwcaps and module masks for double insulation, circuit labels.

To restore the double insulation, use the relative accessories (module masks, screwcaps or wall mounting brackets).

GW40124



## ENCLOSURES AND DISTRIBUTION BOARDS FITTED WITH TERMINAL BLOCKS AND 2 INTERCHANGEABLE FLANGES (1 FLANGE WITH KNOCKOUT HOLES + 1 FLANGE WITH QUICK-ENTRY CABLE GLANDS) - GREY RAL 7035

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Pack<br>Carton |
|-----------|----------------------------|--------------------------|----------------------------------------|----------------------------------------|----------------|
| GW 40 123 | 12                         | 298x260x140              | (3x25)+(10x10)                         | (3x25)+(10x10)                         | 6              |
| GW 40 124 | 24 (12X2)                  | 298x420x140              | (3x25)+(10x10)                         | (3x25)+(10x10)                         | 3              |
| GW 40 125 | 36 (12x3)                  | 298x570x140              | (6x25)+(20x10)                         | (6x25)+(20x10)                         | 2              |

CHARACTERISTICS: the flanges with knockout holes have the following inputs: 4xM16; 4xM20; 3xM25; 1xM32; Glow Wire Test: 750°C

ACCESSORIES SUPPLIED: terminal block, screwcaps and module masks for double insulation, circuit labels.

To restore the double insulation, use the relative accessories (module masks, screwcaps or wall mounting brackets).

## PROTECTED ENCLOSURES IP40

GW40086



## ENCLOSURES AND DISTRIBUTION BOARDS FITTED WITH TERMINAL BLOCKS

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Pack<br>Carton |
|-----------|----------------------------|--------------------------|----------------------------------------|----------------------------------------|----------------|
| GW 40 082 | 8                          | 220x180x100              | (1x25)+(7x10)                          | (1x25)+(7x10)                          | 1/14           |
| GW 40 044 | 12                         | 280x225x100              | (3x25)+(10x10)                         | (3x25)+(10x10)                         | 9              |
| GW 40 046 | 24 (12X2)                  | 280x350x100              | 2x[(1x25)+(7x10)]                      | 2x[(1x25)+(7x10)]                      | 6              |
| GW 40 048 | 36 (18x2)                  | 400x400x130              | 2x[(1x25)+(7x10)]                      | 2x[(1x25)+(7x10)]                      | 2              |
| GW 40 090 | 54 (18x3)                  | 400x550x130              | (6x25)+(20x10)                         | (6x25)+(20x10)                         | 1/2            |
| GW 40 092 | 72 (18x4)                  | 400x850x150              | (12x25)+(40x10)                        | (12x25)+(40x10)                        | 1              |

GW40022



## ENCLOSURES AND DISTRIBUTION BOARDS FITTED WITH TERMINAL BLOCKS

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Pack<br>Carton |
|-----------|----------------------------|--------------------------|----------------------------------------|----------------------------------------|----------------|
| GW 40 022 | 2                          | 45x130x85                |                                        |                                        | 84             |
| GW 40 023 | 4                          | 90x130x85                |                                        |                                        | 36             |
| GW 40 024 | 6                          | 140x155x85               |                                        |                                        | 34             |
| GW 40 025 | 8                          | 180x180x95               | (1x25)+(7x10)                          | (1x25)+(7x10)                          | 24             |
| GW 40 027 | 12+1                       | 250x215x95               | (3x25)+(10x10)                         | (3x25)+(10x10)                         | 12             |
| GW 40 029 | 24+2 (12x2)                | 250x340x95               | 2x[(1x25)+(7x10)]                      | 2x[(1x25)+(7x10)]                      | 12             |
| GW 40 031 | 36+3 (12x3)                | 250x465x95               | 2x[(3x25)+(10x10)]                     | 2x[(3x25)+(10x10)]                     | 9              |

### COMPLEMENTARY ITEMS

|         |                                                                                     |                                                                                                                                                   |                                                     |                             |                                    |
|---------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|-----------------------------|------------------------------------|
| GW44621 |    | <b>WALL FIXING BRACKET</b>                                                                                                                        |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | Material                                            | Accessories supplied        | For enclosures<br>For dist. boards |
|         |                                                                                     | GW 44 621                                                                                                                                         | Insulation                                          | Self-tapping fixing screws  | All wall types                     |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | Pack<br>Carton                     |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 40/480                             |
|         |                                                                                     | APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products. |                                                     |                             |                                    |
| GW40423 |    | <b>4.5 MODULES COVER</b>                                                                                                                          |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | No. of modules<br>EN 50022                          | Colour                      | Characteristics                    |
|         |                                                                                     | GW 40 467                                                                                                                                         | 4,5                                                 | White RAL 9016              | Halogen free                       |
|         |                                                                                     | GW 40 423                                                                                                                                         | 4,5                                                 | Grey RAL 7035               | Halogen free                       |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | Pack<br>Carton                     |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 50                                 |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 50                                 |
|         |                                                                                     | CHARACTERISTICS: clip fixing.                                                                                                                     |                                                     |                             |                                    |
| GW44623 |    | <b>INSULATING SCREW CAPS</b>                                                                                                                      |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | Description                                         | Characteristics             | Pack<br>Carton                     |
|         |                                                                                     | GW 44 623                                                                                                                                         | Screwcap Ø25mm                                      | Halogen free                | 10/100                             |
|         |                                                                                     | APPLICATIONS: used to restore the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.  |                                                     |                             |                                    |
| GW40473 |    | <b>DESIGN COUPLING COVER FOR CONDUIT AND TRUNKING ENTRY FOR CDK ENCLOSURES AND BOARDS</b>                                                         |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | For encl.<br>/boards with rail                      | Fixing                      | Pack<br>Carton                     |
|         |                                                                                     | GW 40 473                                                                                                                                         | 12 Modules                                          | Clip                        | 20                                 |
|         |                                                                                     | GW 40 474                                                                                                                                         | 18 Modules                                          | Clip                        | 20                                 |
|         |                                                                                     | CHARACTERISTICS: covers with internal knockouts for trunking from 60x30mm to 200x60mm.                                                            |                                                     |                             |                                    |
| GW40402 |   | <b>TERMINAL BLOCK WITH INSULATED NEUTRAL AND EARTH BUSBARS FOR ENCLOSURES AND BOARDS</b>                                                          |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | Terminal block<br>N (mm²)                           | Terminal block<br>T (mm²)   | For enclosures                     |
|         |                                                                                     | GW 40 401                                                                                                                                         | (1x25)+(7x10)                                       | (1x25)+(7x10)               | 8 modules EN 50022                 |
|         |                                                                                     | GW 40 402                                                                                                                                         | (3x25)+(10x10)                                      | (3x25)+(10x10)              | 12 modules EN 50022                |
|         |                                                                                     | GW 40 404                                                                                                                                         | (5x25)+(14x10)                                      | (5x25)+(14x10)              | 18 modules EN 50022                |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | Fixing                             |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | With screws                        |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | With screws                        |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | With screws and/or clip            |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | Pack<br>Carton                     |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 10                                 |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 10                                 |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 10                                 |
|         |                                                                                     | ACCESSORIES SUPPLIED: fixing screws.                                                                                                              |                                                     |                             |                                    |
| GW40487 |  | <b>INTERNAL HORIZONTAL DIVIDER FOR CDK BOARDS</b>                                                                                                 |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | For boards<br>EN 50022 rail                         | Fixing                      | Pack<br>Carton                     |
|         |                                                                                     | GW 40 487                                                                                                                                         | 12 Modules                                          | Clip                        | 10/100                             |
|         |                                                                                     | GW 40 488                                                                                                                                         | 18 Modules                                          | Clip                        | 10/100                             |
|         |                                                                                     | CHARACTERISTICS: sealing.                                                                                                                         |                                                     |                             |                                    |
| GW40492 |  | <b>BLANK LID PANELS - 1 MODULE HEIGHT FOR CDKE BOARDS</b>                                                                                         |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | Suitable<br>for                                     | For boards<br>EN 50022 rail | Colour                             |
|         |                                                                                     | GW 40 492                                                                                                                                         | Wall mounting distr. boards                         | 12 Modules                  | Grey RAL 7035                      |
|         |                                                                                     | GW 40 493                                                                                                                                         | Wall mounting distr. boards                         | 18 Modules                  | Grey RAL 7035                      |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | Pack<br>Carton                     |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 20                                 |
|         |                                                                                     |                                                                                                                                                   |                                                     |                             | 20                                 |
|         |                                                                                     | NOTES: they permit making internal separation between the circuits having different voltages located on more than one row inside the same shell.  |                                                     |                             |                                    |
| GW40422 |  | <b>CYLINDER SECURITY LOCK - FOR 40 CDKE ENCLOSURES</b>                                                                                            |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | Material                                            |                             | Pack<br>Carton                     |
|         |                                                                                     | GW 40 421                                                                                                                                         | Insulation                                          |                             | 10/100                             |
|         |                                                                                     | GW 40 422                                                                                                                                         | Pressure die-cast metal                             |                             | 1/10                               |
|         |                                                                                     | ACCESSORIES SUPPLIED: 2 keys.                                                                                                                     |                                                     |                             |                                    |
|         |                                                                                     | NOTES: All the keys and relative locks with the same product code are identical.                                                                  |                                                     |                             |                                    |
| GW40428 |  | <b>INTERCHANGEABLE FLANGE WITH QUICK-ENTRY CABLE GLANDS</b>                                                                                       |                                                     |                             |                                    |
|         |                                                                                     | Code                                                                                                                                              | Entries<br>for flanged                              |                             | Pack<br>Carton                     |
|         |                                                                                     | GW 40 428                                                                                                                                         | 1 for cables Ø 16-29 mm 4 for cables Ø 11-20 mm 8 f |                             | 1/20                               |



## 40 CDe - SURFACE-MOUNTING ENCLOSURES AND DISTRIBUTION BOARDS FOR GERMAN STANDARD

## 40 CDe IP30 WITH TERMINAL BLOCK

GW43022S



## SURFACE-MOUNTING SMALL DISTRIBUTION BOARDS - RAL 9016

| Code        | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Pack<br>Carton |
|-------------|----------------------------|--------------------------|----------------|
| GW 43 021 S | 12                         | 300x245x95               | 1              |
| GW 43 022 S | 24 (12X2)                  | 300x370x95               | 1              |
| GW 43 023 S | 36 (12x3)                  | 300x515x95               | 1              |
| GW 43 024 S | 48 (12x4)                  | 300x640x95               | 1              |

## 40 CDe - GERMAN STANDARD FLUSH-MOUNTING ENCLOSURES

## FOR BRICKWORK WALLS - BLANK DOOR AND METAL FRAME - IP40

GW40152



## ENCLOSURES FOR MASONRY WALLS EQUIPPED WITH TERMINAL BLOCKS - WHITE RAL 9003

| Code      | No. of modules<br>EN 50022 | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Dispersible<br>power (W) | Pack<br>Carton |
|-----------|----------------------------|----------------------------------------|----------------------------------------|--------------------------|----------------|
| GW 40 151 | 12+2                       | (1x25)+(3x16)+(14x10)                  | (1x25)+(3x16)+(14x10)                  | 28                       | 2              |
| GW 40 152 | 24+4 (12x2)                | (2x25)+(6x16)+(16x10)                  | (1x25)+(3x16)+(14x10)                  | 38                       | 2              |
| GW 40 153 | 36+6 (12x3)                | (2x25)+(6x16)+(22x10)                  | (1x25)+(5x16)+(22x10)                  | 48                       | 2              |
| GW 40 154 | 48+8 (12x4)                | (2x25)+(6x16)+(22x10)                  | (1x25)+(5x16)+(22x10)                  | 60                       | 2              |

ACCESSORIES SUPPLIED: labels with self-adhesive pictograms for the identification of services, positioning brackets for masonry of base, mortar guard, certification label.

Enclosures composed by front cover, DIN frame, terminal block and back plastic bottom.

NOTES: dispersible power calculated according to IEC 60670-24.

## FOR PLASTERBOARD WALLS - BLANK DOOR AND METAL FRAME (GWT 850°C) - IP40

GW40162



## ENCLOSURES FOR CAVITY WALLS EQUIPPED WITH TERMINAL BLOCKS - WHITE RAL 9003

| Code      | No. of modules<br>EN 50022 | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | Dispersible<br>power (W) | Pack<br>Carton |
|-----------|----------------------------|----------------------------------------|----------------------------------------|--------------------------|----------------|
| GW 40 161 | 12+2                       | (1x25)+(3x16)+(14x10)                  | (1x25)+(3x16)+(14x10)                  | 16                       | 2              |
| GW 40 162 | 24+4 (12x2)                | (2x25)+(6x16)+(16x10)                  | (1x25)+(3x16)+(14x10)                  | 19                       | 2              |
| GW 40 163 | 36+6 (12x3)                | (2x25)+(6x16)+(22x10)                  | (1x25)+(5x16)+(22x10)                  | 24                       | 2              |
| GW 40 164 | 48+8 (12x4)                | (2x25)+(6x16)+(22x10)                  | (1x25)+(5x16)+(22x10)                  | 27                       | 2              |

CHARACTERISTICS: removable upper part with knockouts for cable entry. Thermo-pressure with ball equal to 70°C.

ACCESSORIES SUPPLIED: terminal block, labels with self-adhesive pictograms for user identification, cable fastener ties, - removable upper wall with pre-cut holes for cable entry (spare part), certification labels.

NOTES: dispersible power calculated according to IEC 60670-24.

Enclosures composed by front cover, DIN frame, terminal block and back plastic bottom.

## COMPLEMENTARY ITEMS

GW43071S



## BLANK DOORS FOR SURFACE-MOUNTING SMALL DISTRIBUTION BOARDS - RAL 9016

| Code        | No. of modules<br>EN 50022 | Colour         | Pack<br>Carton |
|-------------|----------------------------|----------------|----------------|
| GW 43 071 S | 12                         | White RAL 9016 | 1/5            |
| GW 43 072 S | 24 (12X2)                  | White RAL 9016 | 1/10           |
| GW 43 073 S | 36 (12x3)                  | White RAL 9016 | 1/10           |
| GW 43 074 S | 48 (12x4)                  | White RAL 9016 | 1/10           |

GW43082S



## METAL FRAME FOR FLUSH-MOUNTING ENCLOSURES

| Code        | No. of modules<br>EN 50022 | Colour         | Pack<br>Carton |
|-------------|----------------------------|----------------|----------------|
| GW 43 081 S | 12                         | White RAL 9016 | 1              |
| GW 43 082 S | 24 (12X2)                  | White RAL 9016 | 1              |
| GW 43 083 S | 36 (12x3)                  | White RAL 9016 | 1              |
| GW 43 085 S | 48 (12x4)                  | White RAL 9016 | 1              |

GW43055S



## BLANK DOORS FOR FLUSH-MOUNTING ENCLOSURES

| Code        | No. of modules<br>EN 50022 | Colour         | Pack<br>Carton |
|-------------|----------------------------|----------------|----------------|
| GW 43 055 S | 12                         | White RAL 9016 | 1              |
| GW 43 056 S | 24 (12X2)                  | White RAL 9016 | 1              |
| GW 43 057 S | 36 (12x3)                  | White RAL 9016 | 1/5            |
| GW 43 058 S | 48 (12x4)                  | White RAL 9016 | 1              |



GW43047S

### EXTRACTABLE FRAME FOR FLUSH-MOUNTING ENCLOSURE

| Code        | No. of modules<br>EN 50022 | Pack<br>Carton |
|-------------|----------------------------|----------------|
| GW 43 047 S | 24 (12x2)                  | 1              |
| GW 43 048 S | 36 (12x3)                  | 1              |
| GW 43 049 S | 48 (12x4)                  | 1              |



GW43101S

### PLASTIC FRONTAL FOR FLUSH-MOUNTING ENCLOSURES

| Code        | No. of modules<br>EN 50022 | Pack<br>Carton |
|-------------|----------------------------|----------------|
| GW 43 101 S | 12                         | 1              |
| GW 43 102 S | 24 (12x2)                  | 1              |
| GW 43 103 S | 36 (12x3)                  | 1              |
| GW 43 104 S | 48 (12x4)                  | 1              |



GW43111S

### PLASTIC FRONTAL FOR WALL-MOUNTING ENCLOSURES

| Code        | No. of modules<br>EN 50022 | Pack<br>Carton |
|-------------|----------------------------|----------------|
| GW 43 111 S | 12                         | 1              |
| GW 43 112 S | 24 (12x2)                  | 1              |
| GW 43 113 S | 36 (12x3)                  | 1              |
| GW 43 114 S | 48 (12x4)                  | 1              |



GW40451

### TERMINAL BLOCK WITH SUPPORT FOR ENCLOSURES FOR PLASTERBOARD WALLS

| Code      | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | For<br>enclosures | Pack<br>Carton |
|-----------|----------------------------------------|----------------------------------------|-------------------|----------------|
| GW 40 451 | (1x25)+(3x16)+(14x10)                  | (1x25)+(3x16)+(14x10)                  | 12 modules        | 20             |
| GW 40 452 | (2x25)+(6x16)+(16x10)                  | (1x25)+(3x16)+(14x10)                  | 24 modules        | 20             |
| GW 40 453 | (2x25)+(6x16)+(22x10)                  | (1x25)+(5x16)+(22x10)                  | 36-48 modules     | 20             |

CHARACTERISTICS: clip fixing.



GW40461

### PAIR OF JOINTS FOR COMBINED COUPLING OF ENCLOSURES FOR PLASTERBOARD WALLS

| Code      | Fixing | For<br>coupling | Pack<br>Carton |
|-----------|--------|-----------------|----------------|
| GW 40 461 | Clip   | Vertical        | 20             |



GW43041S

### CLOSING SLIDE FOR FLUSH-MOUNTING ENCLOSURES

| Code        | Suitable<br>for              | Pack<br>Carton |
|-------------|------------------------------|----------------|
| GW 43 041 S | Plasterboard wall enclosures | 1              |



GW40457

### INTERNAL DIVIDERS FOR ENCLOSURES FOR PLASTERBOARD WALLS

| Code      | Type of<br>divider | For<br>enclosures   | Fixing | Pack<br>Carton |
|-----------|--------------------|---------------------|--------|----------------|
| GW 40 456 | Vertical           | 12 modules          | Clip   | 50             |
| GW 40 457 | Vertical           | 24 modules          | Clip   | 50             |
| GW 40 458 | Vertical           | 36 modules          | Clip   | 30             |
| GW 40 459 | Vertical           | 48 modules          | Clip   | 20             |
| GW 40 460 | Horizontal         | 12-24-36-48 modules | Clip   | 50             |



GW43045S

### STRAIN RELIEVE RAIL

| Code        | Suitable<br>for           | Pack<br>Carton |
|-------------|---------------------------|----------------|
| GW 43 045 S | Flush mounting enclosures | 10             |



GW43042S

### SEALABLE CLOSURE

| Code        | Suitable<br>for | Pack<br>Carton |
|-------------|-----------------|----------------|
| GW 43 042 S | Wall mounting   | 2/20           |

GW40463



### SAFETY CAPS

| Code      | For enclosures                 | Pack Carton |
|-----------|--------------------------------|-------------|
| GW 40 463 | 40CD German std flush-mounting | 1/10        |

ACCESSORIES SUPPLIED: 2 keys.

NOTES: All the keys and relative locks with the same product code are identical.

GW40467



### 4.5 MODULES COVER - COLOUR WHITE

| Code      | No. of modules EN 50022 | Colour         | Characteristics | Pack Carton |
|-----------|-------------------------|----------------|-----------------|-------------|
| GW 40 467 | 4.5                     | White RAL 9016 | Halogen free    | 50          |

CHARACTERISTICS: clip fixing.

GW43122S



### CIRCUIT LETTERING STRIPS

| Code        | Dimensions (mm) | Pack Carton |
|-------------|-----------------|-------------|
| GW 43 122 S | 265x120         | 10/100      |

GW43044S



### CIRCUIT LETTERING STRIPS

| Code        | Dimensions (mm) | Pack Carton |
|-------------|-----------------|-------------|
| GW 43 044 S | 350x165         | 10/100      |

GW43052S



### ENCLOSURE DOOR LOCK CLOSING SHUTTER

| Code        | Description       | Pack Carton |
|-------------|-------------------|-------------|
| GW 43 052 S | Lock seat shutter | 1/10        |

GW43040S



### SCREW FOR ENCLOSURE FRONT

| Code        | Description                | Pack Carton |
|-------------|----------------------------|-------------|
| GW 43 040 S | Screws for enclosure front | 100         |

### 40 CDe - FRENCH STANDARD MODULAR SURFACE-MOUNTING ENCLOSURES

#### ENCLOSURES WITHOUT DOOR - IP30

GW40501



#### ENCLOSURES EQUIPPED WITH TERMINAL BLOCKS - WALLS WITH KNOCKOUT ELEMENTS - WHITE RAL 9016

| Code      | No. of modules<br>EN 50022 | Outer dim.<br>LxHxD (mm) | Phase terminal<br>block (NxØmm²) | Terminal block<br>N (mm²) | Terminal block<br>T (mm²) | Pack<br>Carton |
|-----------|----------------------------|--------------------------|----------------------------------|---------------------------|---------------------------|----------------|
| GW 40 501 | 13                         | 250x225x93.5             |                                  |                           | E(3x25)+(12x4)            | 8              |
| GW 40 502 | 26 (13x2)                  | 250x350x93.5             | L(1x35)+(5x25)                   | N(1x35)+(5x25)            | E(4x25)+(24x4)            | 4              |
| GW 40 503 | 39 (13x3)                  | 250x475x93.5             | L(1x35)+(5x25)                   | N(1x35)+(5x25)            | E(7x25)+(36x4)            | 4              |
| GW 40 504 | 52 (13x4)                  | 250x600x93.5             | L(1x35)+(5x25)                   | N(1x35)+(5x25)            | E(8x25)+(48x4)            | 2              |

ACCESSORIES SUPPLIED: terminal blocks, module masks, circuit labels with self-adhesive pictograms, instruction sheet.

NOTES: earth terminal blocks with Push-Wire technology.

To restore the double insulation, use the relative accessories (module masks and screwcaps)

#### SUPPORT BASES FOR TARIF BLEU CONNECTING SWITCH

GW40512



#### SUPPORT BASES WITHOUT DOOR FOR EDF CONNECTION SWITCH - PLUMBABLE WHITE RAL 9016

| Code      | Depth | Outer dim.<br>LxHxD (mm) | Pack<br>Carton |
|-----------|-------|--------------------------|----------------|
| GW 40 511 | 40 mm | 250x225x43.5             | 4              |
| GW 40 512 | 55 mm | 250x225x58.5             | 3              |

ACCESSORIES SUPPLIED: fixing screws for the circuit breaker, screwcaps for sealing.

GW40514



#### SUPPORT BASES WITHOUT DOOR FOR THE EDF CONNECTION ONE-WAY SWITCH AND THE ELECTRONIC, SINGLE-PHASE METER - PLUMBABLE - WHITE RAL 9016

| Code      | Depth | Outer dim.<br>LxHxD (mm) | Pack<br>Carton |
|-----------|-------|--------------------------|----------------|
| GW 40 513 | 40 mm | 250x225x47               | 4              |
| GW 40 514 | 55 mm | 250x225x62               | 3              |

ACCESSORIES SUPPLIED: fixing screws for the circuit breaker, instruction sheet, 2x25 mm<sup>2</sup> sectionable cables for connection of enclosure to the circuit breaker.

#### ENCLOSURE FOR CABLE SERVICE DEVICES IP40

GW40515



#### ENCLOSURE FOR CABLE SERVICE DEVICES (T.R.I.) EQUIPPED WITH 2 RAILS EN 50022 AND EARTH TERMINAL BLOCK - WHITE RAL 9016

| Code      | Outer dim.<br>LxHxD (mm) | No. of modules<br>EN 50022 | Terminal block<br>T (mm²) | Pack<br>Carton |
|-----------|--------------------------|----------------------------|---------------------------|----------------|
| GW 40 515 | 250x225x112              | 26 (13x2)                  | 8x16                      | 4              |

ACCESSORIES SUPPLIED: insulating back-mounting plate.

#### COMPLEMENTARY ITEMS

GW40516



#### KIT OF MODULAR SPACERS FOR SUBSCRIBER ENCLOSURES, BASES, CONTAINERS AND BOARDS 50MM THICK - CLIP ASSEMBLY - WHITE RAL 9016

| Code      | Outer dim.<br>LxHxD (mm) | Pack<br>Carton |
|-----------|--------------------------|----------------|
| GW 40 516 | 250x225x50               | 8              |
| GW 40 517 | 250x350x50               | 4              |
| GW 40 518 | 250x475x50               | 4              |
| GW 40 519 | 250x600x50               | 2              |

NOTE: code GW40516 is also suitable for the support bases and containers for services via cable (T.R.I.)

GW40546



#### 2 PIPE FITTINGS FOR VERTICAL AND HORIZONTAL COUPLING OF ENCLOSURES, BASES AND SPACERS

| Code      | Fixing<br>type | Pack<br>Carton |
|-----------|----------------|----------------|
| GW 40 546 | Clip           | 20             |

APPLICATIONS: for creating combined compositions and subscriber boards.

GW40527



#### BACK-MOUNTING PLATES IN INSULATING MATERIAL FOR SURFACE-MOUNTING ENCLOSURES AND SPACER KIT SLIDE FIXING ON RAIL

| Code      | Outer dim.<br>LxHxD (mm) | For<br>enclosures | Pack<br>Carton |
|-----------|--------------------------|-------------------|----------------|
| GW 40 526 | 156x216x2                | 13 mod.- 1 row    | 8              |
| GW 40 527 | 156x341x2                | 26 mod.- 2 rows   | 4              |
| GW 40 528 | 156x466x2                | 39 mod.- 3 rows   | 4              |
| GW 40 529 | 156x591x2                | 52 mod.- 4 rows   | 2              |

GW40530

**INSULATING BACK-MOUNTING PLATES FOR SUPPORT BASES . FIXING TO WALL WITH SCREWS.**

| Code      | Outer dim.<br>LxHxD (mm) | Pack<br>Carton |
|-----------|--------------------------|----------------|
| GW 40 530 | 244x219x2                | 8              |

GW40591

**INSULATING TERMINAL BLOCKS IP20 FOR FRENCH STANDARD MODULAR ENCLOSURES**

| Code      | Type    | Cap<br>colour | Connections<br>no. x section (mm <sup>2</sup> ) | Type<br>of connection | For<br>enclosures | Pack<br>Carton |
|-----------|---------|---------------|-------------------------------------------------|-----------------------|-------------------|----------------|
| GW 40 591 | Earth   | Green         | (3x25)+(12x4)                                   | Push-Wire             | 13M-39M           | 20             |
| GW 40 592 | Earth   | Green         | (4x25)+(24x4)                                   | Push-Wire             | 26M-39M-52M       | 20             |
| GW 40 593 | Phase   | Black         | (1x35)+(5x25)                                   | With screw            | 26M-39M-52M       | 20             |
| GW 40 594 | Neutral | Blue          | (1x35)+(5x25)                                   | With screw            | 26M-39M-52M       | 20             |

CHARACTERISTICS: phase and neutral terminal blocks with In=100A and Vn=450V.

GW40531

**BLANK DOOR WITH FRAME FOR FINISHING FRENCH STANDARD MODULAR ENCLOSURES WITHOUT DOOR  
WHITE RAL 9016 - IP40**

| Code      | For<br>enclosures | Pack<br>Carton |
|-----------|-------------------|----------------|
| GW 40 531 | 13 mod.- 1 row    | 8              |
| GW 40 532 | 26 mod.- 2 rows   | 4              |
| GW 40 533 | 39 mod.- 3 rows   | 4              |
| GW 40 534 | 52 mod.- 4 rows   | 2              |

CHARACTERISTICS: pre-arranged for housing the GW40422 cylinder security locks

GW40536

**TRANSPARENT SMOKED DOOR WITH FRAME FOR FINISHING FRENCH STANDARD MODULAR ENCLOSURES  
WITHOUT DOOR - WHITE RAL 9016 - IP40**

| Code      | For<br>enclosures | Pack<br>Carton |
|-----------|-------------------|----------------|
| GW 40 536 | 13 mod.- 1 row    | 8              |
| GW 40 537 | 26 mod.- 2 rows   | 4              |
| GW 40 538 | 39 mod.- 3 rows   | 4              |
| GW 40 539 | 52 mod.- 4 rows   | 2              |

CHARACTERISTICS: pre-arranged for housing the GW40422 cylinder security locks

GW40542

**DOOR WITH FRAME FOR FINISHING SUPPORT BASES - CLIP FIXING  
WHITE RAL 9016 - IP40**

| Code      | Outer dim.<br>LxHxD (mm) | Door<br>colour     | Pack<br>Carton |
|-----------|--------------------------|--------------------|----------------|
| GW 40 541 | 250x225                  | White RAL 9016     | 4              |
| GW 40 542 | 250x225                  | Smoked Transparent | 4              |

CHARACTERISTICS: pre-arranged for housing the GW40422 cylinder security locks.

GW40422

**CYLINDRICAL SECURITY LOCK - FOR 40 CDE (FRENCH STANDARD) ENCLOSURES**

| Code      | Material                | Pack<br>Carton |
|-----------|-------------------------|----------------|
| GW 40 422 | Pressure die-cast metal | 1/10           |

ACCESSORIES SUPPLIED: 2 keys.

NOTES: All the keys and relative locks with the same product code are identical.

GW44622

**SCREWCAPS IN INSULATING MATERIAL**

| Code      | Description    | For<br>enclosures | Characteristics | Pack<br>Carton |
|-----------|----------------|-------------------|-----------------|----------------|
| GW 44 622 | Screwcap Ø16mm | GW42201           | Halogen free    | 10/100         |

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.

GW40467

**PLASTIC MODULE COVER PROFILE**

| Code      | No. of modules<br>EN 50022 | Colour         | Characteristics | Pack<br>Carton |
|-----------|----------------------------|----------------|-----------------|----------------|
| GW 40 467 | 4.5                        | White RAL 9016 | Halogen free    | 50             |

CHARACTERISTICS: clip fixing.



### 40 CDe - BRITISH STANDARD SURFACE-MOUNTING ENCLOSURES

#### DUAL RCCB SPLIT LOAD - IP30

GW43901



#### ENCLOSURES FOR MODULAR DEVICES WITH WALLS WITH KNOCK-OUT ELEMENTS, SPLIT-LOAD TYPE WITH 2 RESIDUAL CURRENT CIRCUIT BREAKERS - WHITE RAL 9016

| Code      | Total ways | Isolator | RCCB No. 1 (30mA) | RCCB No. 2 (30mA) | Pack Carton |
|-----------|------------|----------|-------------------|-------------------|-------------|
| GW 43 901 | 10 (5+5)   | 100 A    | 63 A              | 63 A              | 1/4         |
| GW 43 902 | 10 (5+5)   | 100 A    | 80 A              | 80 A              | 1/4         |
| GW 43 903 | 12 (6+6)   | 100 A    | 63 A              | 63 A              | 1/4         |
| GW 43 904 | 12 (6+6)   | 100 A    | 80 A              | 80 A              | 1/4         |

**ACCESSORIES SUPPLIED:** no.1 Isolator, no.2 RCCB, terminal block, busbars, shield IPxB for connecting live parts and cover pads, module mask and circuit label.

**NOTES:** to maintain the IP degree declared, install devices with a degree of protection of at least IP40 and use the relative accessories (module masks, screw caps or wall mounting brackets).

To restore the double insulation, use the relative accessories (module masks, screw caps or wall mounting brackets).

Door fitted to accommodate security cylinder lock code: GW40422.

Products in accordance with the BS7671 - 17th edition + emendament 2011.

**CHARACTERISTICS:** NEUTRAL TERMINAL BLOCKS (N°xmm<sup>2</sup>): 2x[(2x25)+(6x16)]; EARTH TERMINAL BLOCKS (N°xmm<sup>2</sup>): (3x25)+(12x16).

GW43911



#### ENCLOSURES FOR MODULAR DEVICES WITH WALLS WITH KNOCK-OUT ELEMENTS, SPLIT-LOAD TYPE WITH 2 RESIDUAL CURRENT CIRCUIT BREAKERS PLUS A NON- PROTECTED CIRCUIT - WHITE RAL 9016

| Code      | Total ways | Isolator | RCCB No. 1 (30mA) | RCCB No. 2 (30mA) | Pack Carton |
|-----------|------------|----------|-------------------|-------------------|-------------|
| GW 43 911 | 10 (2+4+4) | 100 A    | 63 A              | 63 A              | 1/4         |
| GW 43 912 | 12 (2+5+5) | 100 A    | 63 A              | 63 A              | 1/4         |

**ACCESSORIES SUPPLIED:** no.1 Isolator, no.2 RCCB, terminal block, busbars, shield IPxB for connecting live parts and cover pads, module mask and circuit label.

**NOTES:** to maintain the IP degree declared, install devices with a degree of protection of at least IP40 and use the relative accessories (module masks, screw caps or wall mounting brackets).

To restore the double insulation, use the relative accessories (module masks, screw caps or wall mounting brackets).

Door fitted to accommodate security cylinder lock code: GW40422.

Products in accordance with the BS7671 - 17th edition + emendament 2011.

**CHARACTERISTICS:** NEUTRAL TERMINAL BLOCKS (N°xmm<sup>2</sup>): 2x[(1x25)+(6x16)]+[(2x25)+(2x16)]; EARTH TERMINAL BLOCKS (N°xmm<sup>2</sup>): (3x25)+(12x16).

GW43921



#### ENCLOSURES FOR MODULAR DEVICES WITH WALLS WITH KNOCK-OUT ELEMENTS, SPLIT-LOAD TYPE WITH 3 RESIDUAL CURRENT CIRCUIT BREAKERS - WHITE RAL 9016

| Code      | Total ways | Isolator | RCCB No. 1 (30mA) | RCCB No. 2 (30mA) | RCCB No. 3 (30mA) | Pack Carton |
|-----------|------------|----------|-------------------|-------------------|-------------------|-------------|
| GW 43 921 | 10 (2+4+4) | 100 A    | 80 A              | 80 A              | 40 A              | 1/4         |

**ACCESSORIES SUPPLIED:** no.1 Isolator, no.3 RCCB, terminal block, busbars, shield IPxB for connecting live parts and cover pads, module mask and circuit label.

**NOTES:** to maintain the IP degree declared, install devices with a degree of protection of at least IP40 and use the relative accessories (module masks, screw caps or wall mounting brackets).

To restore the double insulation, use the relative accessories (module masks, screw caps or wall mounting brackets).

Door fitted to accommodate security cylinder lock code: GW40422.

Products in accordance with the BS7671 - 17th edition + emendament 2011.

**CHARACTERISTICS:** NEUTRAL TERMINAL BLOCKS (N°xmm<sup>2</sup>): 2x[(1x25)+(6x16)]+[(2x25)+(2x16)]; EARTH TERMINAL BLOCKS (N°xmm<sup>2</sup>): (3x25)+(12x16).

#### SURFACE-MOUNTING

GW40023



#### ENCLOSURES PRE-FITTED FOR TERMINAL BLOCK HOUSING WITH WALLS WITH KNOCKOUT HOLES GREY RAL 7035

| Code      | No. of modules EN 50022 | Outer dim. LxHxD (mm) | Dispersible power (W) | Pack Carton |
|-----------|-------------------------|-----------------------|-----------------------|-------------|
| GW 40 023 | 4                       | 90x130x85             | 9                     | 36          |
| GW 40 026 | 8                       | 180x180x95            | 18                    | 24          |

**ACCESSORIES SUPPLIED:** module masks, circuit labels.

**NOTES:** dispersible power calculated according to IEC 60670-24.

## COMPLEMENTARY ITEMS

|                                                                                                                                                   |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |
|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------|----------------------------------------|---------------------------------------|----------------|
| GW40851                                                                                                                                           |    | SINGLE-POLE COMB FOR CONNECTING MODULAR DEVICES                                                                       |                                        |                                        |                                       |                |
|                                                                                                                                                   |                                                                                     | Code                                                                                                                  | No. of modules<br>EN 50022             | Rated<br>current (A)                   | No.<br>cable inlets                   | No.<br>outputs |
|                                                                                                                                                   |                                                                                     | GW 40 851                                                                                                             | 17                                     | 100                                    | 1                                     | 16             |
| CHARACTERISTICS: specifically designed for GEWISS British Standard enclosures.                                                                    |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |
| GW43971                                                                                                                                           |    | NEUTRAL AND EARTH TERMINAL BLOCKS WITH SUPPORT FOR BRITISH STANDARD ENCLOSURES<br>CONSUMER UNIT - SCREW FIXING - IP00 |                                        |                                        |                                       |                |
|                                                                                                                                                   |                                                                                     | Code                                                                                                                  | Terminal block<br>N (mm <sup>2</sup> ) | Terminal block<br>T (mm <sup>2</sup> ) | For<br>enclosures                     | Pack<br>Carton |
|                                                                                                                                                   |                                                                                     | GW 43 971                                                                                                             | 2x[(2x25)+(6x16)]                      | (3x25)+(12x16)                         | GW43901 - GW43902 - GW43903 - GW43904 | 20             |
|                                                                                                                                                   |                                                                                     | GW 43 972                                                                                                             | 2x[(1x25)+(6x16)]                      | (3x25)+(12x16)                         | GW43911 - GW43912                     | 20             |
|                                                                                                                                                   |                                                                                     | GW 43 973                                                                                                             | 2x[(1x25)+(6x16)] + 1x[(2x25)+(2x16)]  | (3x25)+(12x16)                         | GW43921                               | 20             |
| ACCESSORIES SUPPLIED: fixing screws.                                                                                                              |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |
| GW43981                                                                                                                                           |    | PAIR OF CABLES FOR PHASE AND NEUTRAL, FOR BRITISH STANDARD ENCLOSURES - CONSUMER UNIT                                 |                                        |                                        |                                       |                |
|                                                                                                                                                   |                                                                                     | Code                                                                                                                  | Nominal<br>sections (mm <sup>2</sup> ) | Neutral<br>cable                       | Phase<br>cable                        | Pack<br>Carton |
|                                                                                                                                                   |                                                                                     | GW 43 981                                                                                                             | 20                                     | Blue - 1x0.40m                         | Brown - 1x0.37m                       | 1/50           |
| CHARACTERISTICS: cables with stripped and fitted ends.                                                                                            |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |
| GW96045                                                                                                                                           |    | MODULE BLANKING PIECES AND BUS BAR COVER                                                                              |                                        |                                        |                                       |                |
|                                                                                                                                                   |                                                                                     | Code                                                                                                                  | Description                            |                                        |                                       | Pack<br>Carton |
|                                                                                                                                                   |                                                                                     | GW 96 045                                                                                                             | Set of 5 module cap with pedicel caps  |                                        |                                       | 1/50           |
| GW40422                                                                                                                                           |   | CYLINDRICAL SECURITY LOCK - FOR 43 CD CONSUMER UNITS                                                                  |                                        |                                        |                                       |                |
|                                                                                                                                                   |                                                                                     | Code                                                                                                                  | Material                               |                                        |                                       | Pack<br>Carton |
|                                                                                                                                                   |                                                                                     | GW 40 422                                                                                                             | Pressure die-cast metal                |                                        |                                       | 1/10           |
| ACCESSORIES SUPPLIED: 2 keys.                                                                                                                     |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |
| NOTES: All the keys and relative locks with the same product code are identical.                                                                  |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |
| GW44621                                                                                                                                           |  | FIXING BRACKET FOR SURFACE-MOUNTING, WITH SELF-TAPPING SCREWS - FOR 43 CD CONSUMER UNITS                              |                                        |                                        |                                       |                |
|                                                                                                                                                   |                                                                                     | Code                                                                                                                  | Characteristics                        |                                        |                                       | Pack<br>Carton |
|                                                                                                                                                   |                                                                                     | GW 44 621                                                                                                             | Halogen free                           |                                        |                                       | 40/480         |
| APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products. |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |
| GW44623                                                                                                                                           |  | SCREWCAPS IN INSULATING MATERIAL                                                                                      |                                        |                                        |                                       |                |
|                                                                                                                                                   |                                                                                     | Code                                                                                                                  | Description                            | Suitable<br>for                        | Material                              | Pack<br>Carton |
|                                                                                                                                                   |                                                                                     | GW 44 623                                                                                                             | Screwcap Ø25mm                         | All 43 CD Consumer units range         | Halogen free                          | 10/100         |
| APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products. |                                                                                     |                                                                                                                       |                                        |                                        |                                       |                |